

NO	MODEL	TANK VOLUME (lt)	AIR SUCTION CAPACITY (lt/min)	PRESSURE (bar)	NUMBER OF CYLINDER	CYLINDER DIAMETER (mm)	MOTOR POWER (HP)	DIMENSIONS			WEIGHT (kg)
								W	L	H	
SINGLE STAGE		(cm)									
1	TK-25/50	25	100	8	1	50	1(220V)	300	600	600	30
2	TK-50/50	50	100	8	1	50	1(220V)	360	700	700	38
3	TK-100/70 M	100	200	8	1	70	1,5(220V)	550	1200	980	92
4	TK-100/70	100	200	8	1	70	1,5	550	1200	980	92
5	TK-150/2X60 M	150	300	8	2	60-60	1,5(220V)	550	1300	880	106
6	TK-150/2X60	150	300	8	2	60-60	1,5	550	1300	880	106
7	TK-200/2X70 M	200	340	8	2	70-70	2(220V)	550	1500	1050	150
8	TK-200/2X70	200	340	8	2	70-70	2	550	1500	1050	150
9	TK-200/2X70-3	200	400	8	2	70-70	3	550	1500	1050	150
10	TK-300/2X90	300	500	8	2	90-90	4	560	1700	1030	187
11	TK-300/2X90-5*	300	550	8	2	90-90	5,5	560	1700	1050	190
12	TK-400/2X110*	400	750	8	2	110-110	5,5	650	1950	1270	280
13	TK-400/3X90*	400	820	8	3	3x90	5,5	650	1960	1220	303
14	TK-500/2X110*	500	750	8	2	110-110	7,5	650	1950	1380	326
15	TK-500/3X90*	500	900	8	3	3x90	7,5	650	1950	1380	326
16	TK-500/3X110*	500	1150	8	3	3x110	7,5	650	1950	1380	350
17	TK-500/3X110-10**	500	1270	8	3	3x110	10	650	1950	1380	355
18	TK-1000/2X110-15**	1000	1500	8	4	2x(110-110)	15	1200	2000	1700	700
19	TK-1000/3X110-20**	1000	2300	8	6	2x(3x110)	20	1200	2000	1750	710