TK • CK







Easy to use and Quality Equipment

- Low speed
- Highly efficient and long-lasting
- Low noise level
- Ideal and ergonomic head structure
- Durable to heavy conditions and continuous operation
- Cast iron cylinder and cylinder covers
- Ductile cast iron crankshaft
- Special alloy aluminum piston rods
- Special alloy cast iron body
- Electric box suitable for compressor



Piston Air Compressors



СК

MODEL	Tank Volume	Air Intake	Pressure	Number of Cylinders	Cylinder Diameter	Motor Power	Dimensions			
							Width	Length	Height	Weight
TWO STAGE		(lt/min.)	(bar)			(HP)				(kg)
CK-200/90X60	200	325	12	2	90x60	4	550	1500	1050	150
CK-300/110X70*	300	375	12	2	110-70	5.5	550	1700	1230	260
CK-500/2X90X60*	500	550	12	3	2x90-60	5.5	650	1950	1320	320
CK-500/2X110X70*	500	750	12	З	2x110-70	7.5	650	1950	1380	360

- Compressor performance is measured according to ISO 1217: 2009 Annex C with reference to 1 bar inlet pressure and 20 ° C ambient temperature.

- * Control box is included.

- ** Star-Delta control box is excluded, should be requested separately.