

# ODR HP Series High Pressure Air Dryers

## ODR HP Series



Ozen Kompresor dryers, which stand out with their efficiency and durability, have set a standard with their performance. Patented and uniquely designed heat exchangers are produced from corrosion resistant and high strength thick stainless tubes.

- Long-lasting heat exchangers with quality materials and robust design.
- Air perforated copper plates welded to steel tubes with the latest technology
- Low pressure drop provides energy savings and reduces operating costs.
- Responds to all capacity and power needs
- The footprint is small with its small and compact design.



## Technical Specifications

MODEL	Flow (m3/min)	Flow (m3/h)	Voltage V / ~ / Hz	Inlet - Outlet Connection Size	Recommended Filters	Max. Working Pressure (Bar)	Max. Ambient Temperature °C	Max. Inlet Temperature °C
ODR 50 HP	0,83	50	230V / 1 / 50 Hz	3/4"	OFL 100 HG-MX-MY-MA	50	55	60
ODR 90 HP	1,50	90	230V / 1 / 50 Hz	3/4"	OFL 100 HG-MX-MY-MA	50	55	60
ODR 150 HP	2,50	150	230V / 1 / 50 Hz	3/4"	OFL 300 HG-MX-MY-MA	50	55	60
ODR 220 HP	3,67	220	230V / 1 / 50 Hz	3/4"	OFL 300 HG-MX-MY-MA	50	55	60
ODR 300 HP	5,00	300	230V / 1 / 50 Hz	1 1/4"	OFL 300 HG-MX-MY-MA	50	55	60
ODR 400 HP	6,67	400	230V / 1 / 50 Hz	1 1/4"	OFL 600 HG-MX-MY-MA	50	55	60
ODR 500 HP	8,33	500	230V / 1 / 50 Hz	1 1/4"	OFL 600 HG-MX-MY-MA	50	55	60
ODR 575 HP	9,58	575	230V / 1 / 50 Hz	1 1/4"	OFL 600 HG-MX-MY-MA	50	55	60
ODR 775 HP	12,92	775	230V / 1 / 50 Hz	1 1/4"	OFL 850 HG-MX-MY-MA	50	55	60
ODR 910 HP	15,17	910	230V / 1 / 50 Hz	1 1/4"	OFL 1200 HG-MX-MY-MA	50	55	60
ODR 1000 HP	16,67	1000	230V / 1 / 50 Hz	2"	OFL 1200 HG-MX-MY-MA	50	55	60
ODR 1160 HP	19,33	1160	230V / 1 / 50 Hz	2"	OFL 1200 HG-MX-MY-MA	50	55	60
ODR 1500 HP	25,00	1500	230V / 1 / 50 Hz	2"	OFL 1600 HG-MX-MY-MA	50	55	60
ODR 1600 HP	26,67	1600	400V / 3 / 50 Hz	2"	OFL 1600 HG-MX-MY-MA	50	55	60
ODR 1800 HP	30,00	1800	400V / 3 / 50 Hz	2"	OFL 2500 HG-MX-MY-MA	50	55	60
ODR 2200 HP	36,67	2200	400V / 3 / 50 Hz	2 1/2"	OFL 2500 HG-MX-MY-MA	50	55	60
ODR 2500 HP	41,67	2500	400V / 3 / 50 Hz	2 1/2"	OFL 2500 HG-MX-MY-MA	50	55	60
ODR 2700 HP	45,00	2700	400V / 3 / 50 Hz	2 1/2"	OFL 3000 HG-MX-MY-MA	50	55	60
ODR 3000 HP	50,00	3000	400V / 3 / 50 Hz	2 1/2"	OFL 3000 HG-MX-MY-MA	50	55	60
ODR 3300 HP	55,00	3300	400V / 3 / 50 Hz	2 1/2"	OFL 3000 HG-MX-MY-MA	50	55	60
ODR 3600 HP	60,00	3600	400V / 3 / 50 Hz	2 1/2"	OFL 3000 HG-MX-MY-MA	50	55	60

- Capacities are specified according to ISO 1217: 2009 Annex C with reference to 1 bar inlet pressure and 20 °C ambient temperature. Dew point is +3 °C.

Pressure ( Bar )	20	25	30	35	40	45	50	-	-	-	-
F1	1.19	1.1	1.07	1.04	1.02	1	0.98	-	-	-	-
Ambient Temperature °C	-	-	-	-	20	25	30	35	40	42	-
F2	-	-	-	-	0.93	1	1.07	1.15	1.22	1.27	-
Inlet Temperature °C	-	-	-	-	30	35	40	45	50	55	60
F3	-	-	-	-	0.83	1	1.18	1.38	1.59	1.83	2.04

- Max. Pressure 50 Barg - Nominal Working Pressure 40 Barg