

Ozen Kompressor TK-CK piston compressor series is designed to provide reliable and high-quality compressed air source in different industrial applications. TK and CK series piston compressors that meet the uninterrupted air requirement of small businesses, increase your productivity with easy access to spare parts and low maintenance costs. All models in high-quality piston compressor series offer mobility, low noise level and ease of use.

AUTO
REPAIR-PAINT

TEXTILE
WORKSHOP

TIRE
REPAIRER

FURNITURE
CARPENTRY



Easy to use and Quality Equipment

- Low speed
- Highly efficient and long-lasting
- Low noise level
- Ideal and ergonomic head structure
- Durable to heavy conditions and continuous operation
- Cast iron cylinder and cylinder covers
- Ductile cast iron crankshaft
- Special alloy aluminum piston rods
- Special alloy cast iron body
- Electric box suitable for compressor



Piston Compressor Series

TK

MODEL	Tank Volume	Air Intake	Pressure	Number of Cylinders	Cylinder Diameter	Motor Power	Dimensions			Weight
							Width	Length	Height	
SINGLE STAGE	(lt)	(lt/min.)	(bar)		(mm)	(HP)	(mm)			(kg)
TK-100/70 M	100	200	8	1	70	1,5 (220V)	550	1200	980	92
TK-100/70	100	200	8	1	70	1.5	550	1200	980	92
TK-150/2X60 M	150	300	8	2	60-60	1,5 (220V)	550	1300	880	106
TK-150/2X60	150	300	8	2	60-60	1.5	550	1300	880	106
TK-200/2X70 M	200	340	8	2	70-70	2 (220V)	550	1500	1050	150
TK-200/2X70	200	340	8	2	70-70	2	550	1500	1050	150
TK-200/2X70-3	200	400	8	2	70-70	3	550	1500	1050	150
TK-300/2X90	300	500	8	2	90-90	4	560	1700	1030	187
TK-300/2X91-5*	300	700	8	2	90-90	5.5	560	1700	1050	190
TK-500/2X91- 5	500	700	8	2	90-90	5.5	650	1950	1380	326
TK-500/2X110*	500	750	8	2	110-110	7.5	650	1950	1380	326
TK-500/3X90*	500	900	8	3	3x90	7.5	650	1950	1380	326
TK-500/3X110*	500	1150	8	3	3x110	7.5	650	1950	1380	350
TK-500/3X110-10**	500	1270	8	3	3x110	10	650	1950	1380	355

- Compressor performance is measured according to ISO 1217: 2009 Annex C with reference to 1 bar inlet pressure and 20 ° C ambient temperature.

- * Control box is included.

- ** Star-Delta control box is excluded, should be requested separately.